REPORT DOCUMENTATION PAGE

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for rev

AFRL-SR-BL-TR-00-

rubic reporting oursel for this collection of information is estimated to average. I nour per response, including the time for fevi maintaining the date needed, and completing and reviewing this collection of information. Send comments regarding this burde suggestions for reducing this burden to Department of Defense, Washington Headquarters Services. Prectorate for Information Suite 1204, Arlington, VA. 22202-4302. Respondents should be aware that notwithstanding any of the provision of law, no be collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO 3. DATES COVERED (From - To) 2. REPORT TYPE 1. REPORT DATE (DD-MM-YYYY) 15-04-1999 - 14-04-2000 Final Technical 11-09-2000 5a. CONTRACT NUMBER 4. TITLE AND SUBTITLE (U) Novel Extended-Wavelength Diode Lasers to Enable 5b. GRANT NUMBER Sensitive Detection of CO and NOx F49620-99-1-0247 5c. PROGRAM ELEMENT NUMBER 61103D 5d. PROJECT NUMBER 6. AUTHOR(S) 3484 Ronald K. Hanson 5e. TASK NUMBER 5f. WORK UNIT NUMBER 8. PERFORMING ORGANIZATION REPORT 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) NUMBER Stanford University Mechanical Engineering Department Stanford CA 94305-3032 10. SPONSOR/MONITOR'S ACRONYM(S) 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NA 801 North Randolph Street 11. SPONSOR/MONITOR'S REPORT Room 732 NUMBER(S) Arlington VA 22203-1977 12. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited

13. SUPPLEMENTARY NOTES

14. ABSTRACT

15. SUBJECT TERMS

Equipment was acquired under the Defense University Research Instrumentation Program (DURIP). The equipment, summarized in the report, was utilized to extend the measurement capabilities of diode laser spectroscopy to include carbon monoxide and oxides of nitrogen. These species are of particular importance as indicators of airbreathing propulsion performance and because they are subject to environmental regulation.

20001016 013

diode lase	er spectroscopy	, combustion,	diagnostics			
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON Julian M. Tishkoff	
a.REPORT Unclassified	b. ABSTRACT Unclassified	c.THIS PAGE Unclassified	UL	5	19b. TELEPHONE NUMBER (include area code) (703) 696 - 8478	

TABLE OF CONTENTS

1.0 OVERVIEW	3
2.0 EQUIPMENT ACQUIRED	
3.0 RESEARCH ENABLED	غ
Table 2.1: Equipment Acquired	5

DURIP/Instrumentation Grant Final Technical Report

Ronald Hanson Department of Mechanical Engineering Stanford University, Stanford, CA 94305-3032

1.0 OVERVIEW

This final technical report identifies and describes equipment acquired under AFOSR Grant F49620-99-1-0247 and summarizes the research for which the equipment will be used. The total grant amount including cost sharing was \$145,317.00.

2.0 EQUIPMENT ACQUIRED

A description of each item acquired, its manufacturer and cost is given in Table 2.1.

The equipment purchased can be divided into three laser systems and a data acquisition system:

Laser System 1: providing 390 nm radiation;

Laser System 2: providing 306 nm frequency modulated radiation.;

Laser System 3: providing 760 and 1623 nm IR and near IR radiation.

Data Acquisition System.

3.0 RESEARCH ENABLED

Each laser system enables researchers in our group to access wavelengths needed to develop detection schemes for key combustion and atmospheric species.

Laser system 1 provides access to transitions near 390 nm enabling detection of NO_X species. This system has already been applied to the quantitative detection of NO_2 in a shock tube and a static cell. This wavelength regime is also useful for the detection of CH and CN radicals.

Laser system 2 provides the ability to frequency modulate (FM) 306 nm laser radiation. This FM scheme combined with a quieter 532 nm pump laser should offer a 10x improved detection limit for OH radicals. Once this system is functional at 306 nm, we will extend its range of operation to include 225 nm, for the detection of NO.

Laser system 3 takes advantage of VCSEL (Vertical cavity surface emitting diode lasers) and DFB (Distributed feedback) lasers to generate radiation at 760 and 1623 nm. The present scheme should enable quantitative detection of O_2 and C_2H_4 in combustion

flows at multiple locations. These VCSELs have the capability to scan quite widely in wavelength space, and this permits the investigation of the spectral parameters of pressure-broadened lines. Quantitative O_2 measurements have been performed in a cell over a wide range of pressures using this equipment.

The increase in the number of diagnostic wavelengths requires an increase in our data acquisition capacity. This is supplied by the new data acquisition system.

Table 2.1: Equipment Acquired

No.	Description	Manufacturer	Cost (\$)			
	System 1					
1	Tunable diode laser	PolyTec PI	10,600			
	System 2					
2	Solid state pump laser	Coherent Laser Group	51,600			
3	Electro-optic modulator	Quantum Technology	22,700			
4	Microwave amplifier	Amplifier Research	17,100			
5	GHz signal generator	Agilent Technologies	16,300			
	System 3a VCSEL Laser	rs				
6	VCSEL lasers	CSEM CH-8048	2,200			
	Supporting optics and	Mueller Optics, New	11,400			
	accessories including:	Focus, Horibastec,				
	optical windows, mirrors,	Photo Technology,				
	mass flow controller,	Thorlabs Inc.				
	xenon lamp, Si detector					
	System 3b DFB Lasers					
7	DFB 1624nm lasers	Sumitomo Electric	1,200			
	Supporting optics and	Edmund Scientific, Oz	3,200			
	accessories including:	Optics, Imageologists,				
	grating, fiber optics,	Janos Technology,				
	digital camera,	Melles Griot				
	multiplexing prism, beam					
	splitter					
	Data Acquisition System		•			
8	D/A Card	National Instruments	6,700			
9	Computer	Dell Computer	2,400			
		TOTAL	\$145,400			